






THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AMPHENOL CABLES ON DEMAND. ANY REPRODUCTION OR DISCLOSURE TO THIRD PARTIES IN PART OR WHOLE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF AMPHENOL CABLES ON DEMAND IS PROHIBITED.

REV.	DESCRIPTION	DATE	APPROVED
A	NEW RELEASE	23/MAY/2007	
A1	Add 360° Copper-Foil Shield	21/MAY/2007	
A2	Add wiring color	16/JAN/2012	

4-40thread(UNC)




4X THUMBSCREW

LENGTH



D-SUB
25PIN Male

D-SUB
25PIN Male



PIN OUT:

Male	Male	Color
PIN1	PIN1	Black
PIN2	PIN2	Brown
PIN3	PIN3	Red
PIN4	PIN4	Orange
PIN5	PIN5	Yellow
PIN6	PIN6	Green
PIN7	PIN7	Blue
PIN8	PIN8	Purple
PIN9	PIN9	Gray
PIN10	PIN10	White
PIN11	PIN11	Pink
PIN12	PIN12	Light green
PIN13	PIN13	Black/white
PIN14	PIN14	Brown/white
PIN15	PIN15	Red/white
PIN16	PIN16	Orange/white
PIN17	PIN17	Green/white
PIN18	PIN18	Blue/white
PIN19	PIN19	Purple/white
PIN20	PIN20	Red/black
PIN21	PIN21	Orange/black
PIN22	PIN22	Yellow/black
PIN23	PIN23	Green/black
PIN24	PIN24	Gray/black
PIN25	PIN25	Pink/black
SHIELD	SHIELD	Drain Wire

LENGTH & P/N Table

LENGTH	P/N	Cable Color
2.5FT ±1 inch	CS-DSLSZH25MM-002.5	BLACK
5FT ±2 inch	CS-DSLSZH25MM-005	BLACK
10FT ±3 inch	CS-DSLSZH25MM-010	BLACK
15FT ±3 inch	CS-DSLSZH25MM-015	BLACK
25FT ±4 inch	CS-DSLSZH25MM-025	BLACK
50FT ±6 inch	CS-DLSLSZH25MM-050	BLACK
125FT ±8 inch	CS-DLSLSZH25MM-125	BLACK

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
DECIMALS ANGLES
X ±.X ±.X°
XX ±.XX
XXX ±.XXX



THIRD ANGLE PROJECTION		APPROVALS		DATE		Amphenol Cables on Demand 20 VALLEY ST. ENDICOTT, NY 13760	
DRAWN		LF		16/JAN/2012		LSZH Data Cable 25 PIN D-Sub MM	
CHECKED		BA		16/JAN/2012			
MFG ENG		RESV ENG				SIZE DWG. NO. CS-DLSLSZH25MM-XXX	
SCALE		SHEET		OF		REV. A2	

NOTES: UNLESS OTHERWISE SPECIFIED