



Connectors > Connector Accessories > Connector Seals & Cavity Plugs



Connector Seal & Plug Type: **Cable Seal**

Operating Temperature Range: **-40 – 150 °C [-40 – 302 °F]**

Primary Product Color: **Red**

Primary Product Material: **Silicone**

Compatible Insulation Diameter Range: **1.35 – 2.1 mm [.053 – .083 in]**

Features

Product Type Features

Connector Seal & Plug Type	Cable Seal
----------------------------	------------

Body Features

Primary Product Color	Red
Primary Product Material	Silicone

Dimensions

Compatible Insulation Diameter Range	1.35 – 2.1 mm[.053 – .083 in]
--------------------------------------	-------------------------------

Usage Conditions

Operating Temperature Range	-40 – 150 °C[-40 – 302 °F]
Operating Temperature (Max)	150 °C[302 °F]

Other

Resistance to Hydrocarbons	Poor
Shore A Hardness	50
Contains Lubricant	Yes

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) SVHC > Threshold: Dodecamethylcyclohexasiloxane (D6) (.5% in M-12758-1) Decamethylcyclopentasiloxane (D5) (.5% in M-12758-1) Octamethylcyclotetrasiloxane (D4) (.5% in M-11817-1) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

 TE Part # 1488992-2 3P FML ASSY,SEAL,LOW,B KEY, NOCPA,ALLOPEN	 TE Part # 1488992-1 3P FML ASSY,SEAL,LOW,A KEY, NOCPA,ALLOPEN	 TE Part # 2347894-1 16POS,AMP MCP 1.5K,REC HSG ASSY, COD A	 TE Part # 2347894-2 16POS,AMP MCP 1.5K,REC HSG ASSY, COD B
--	---	---	---



TE Part # 2098559-8
6POS, MCON 1.2 CB REC 2p TL
SEALED

TE Part # 4-2098557-2
2P,FML,1.2,CB,MCON,T4,STD,KEYB,w
/LgCPA

TE Part # 2098641-7
2POS, MCON 1.2 CB REC 2p SL
SEALED

TE Part # 2098559-7
6POS, MCON 1.2 CB REC 2p TL
SEALED

TE Part # 2301461-2
30POS,HYBRID,TAB HSG ASSY,SLD,
COD B

TE Part # 4-2098559-1
6P,FML,1.2,CB,MCON,STD,KEYA,T4,w
/LgCPA

TE Part # 1-2098559-2
6P,1.2,CB,MCON,Ky D,CPA,HT,
BlockedCav

TE Part # CAT-N14-RC4812
48V Ready 1.2mm Sealed Connectors

TE Part # 1-2291436-2
PLUG ASS'Y, 2P SL, INJECT, KEY B,
CPA

TE Part # CAT-M4595-T273
MCON Receptacle and Tab

Also in the Series

MCON Interconnection System

Automotive Connector Locks & Position Assurance(16)

Automotive Housings(117)

Automotive Seals & Cavity Plugs(12)

Automotive Signal & Power Connector Housings(116)

Other Automotive Connector Accessories(1)

Customers Also Bought





TE Part #182485-4
FF 187 REC 0.5-1.5MM2 TPPB LP



TE Part #184095-1
RECPT, CONTACT .070, AUPHBZ



TE Part #184344-1
2X2 PLG ASY KEY A C3




TE Part #968679-2
MPQ 2.8 Sn Tab. LL unsealed >0.35-0.5 mm2




TE Part #1670146-1
MCON 1.2 CB REC SWS SN



TE Part #2203771-1
3POS, MCON 1.2 CB REC 1p TL SEALED



TE Part #2350493-1
179POS,0.5 SERIES,REC HSG,LEVER



TE Part #2350506-1
99POS,0.5 SERIES,REC HSG,LEVER



TE Part #2350507-2
99POS,0.5 SERIES,REC HSG,WIRE COVER



TE Part #2394137-1
025/060 HYB 4P CAP

Documents

Product Drawings

WIRE SEAL,RUBBER,SENSOR, RED

English

CAD Files

Customer View Model

ENG_CVM_CVM_2098582-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2098582-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2098582-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications



Application Specification

English