928948-4 × OBSOLETE

FASTIN-FASTON | FASTIN-FASTON 250

TE Internal #: 928948-4

TE Internal Description: FF 250 TAB 17-13 AWG .015 TPPB

View on TE.com >

Terminals & Splices > Quick Disconnects







Quick Disconnect Terminal Type: **Tab**

Wire Size: **1.03 – 2.62 mm²**

Mating Tab Width: **6.35 mm [.25 in]**

Mating Tab Thickness: **.81 mm [.032 in]**

Features

Configuration Features

Compatible With Wire & Cable Type	Discrete Wire
Connection Capacity	Single

Contact Features

Quick Disconnect Terminal Type	Tab
Mating Tab Width	6.35 mm[.25 in]
Mating Tab Thickness	.81 mm[.032 in]
Terminal Orientation	Straight
Contact Base Material	Phosphor Bronze
Terminal Plating Material	Tin
Crimp Type	F-Crimp
Barrel Type	Open

Termination Features

Product Terminates To	Wire & Cable

Mechanical Attachment

Locking Lance Height	1.5 mm[.06 in]
Wire Insulation Support	With

Mating Retention Type	Dimple

Dimensions

Product Length	28 mm[1.1 in]
Compatible Insulation Diameter Range	2.4 – 3.7 mm[.094 – .145 in]
Terminal Material Thickness	.4 mm[.015 in]
Wire Size	1.03 – 2.62 mm²

Usage Conditions

Insulation Option	Uninsulated
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]

Packaging Features

Packaging Quantity	1500
Packaging Method	Loose Piece/Carton

Other

Line	FASTIN-FASTON .250

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Also in the Series | FASTIN-FASTON 250



Crimp Terminal Housings(192)



Insertion & Extraction Tools(2)




Quick Disconnects(217)

Customers Also Bought




TE Part #1SNG609011R0000
ENBR-WG-M16-BL-A



TE Part #364214-E
SRCBUG A 2,54 2 3 CSI 164 E1 ADV J 2 324




TE Part #32835
PIDG R 22-16 COMM 22-18 MIL 8



TE Part #170341-3
FF 250 TAB 14-12AWG PTBR WITHOUT LATCH



TE Part #182647-1
11-4 CPC PLUG



TE Part #280099
FF 250 TAB HSG 8P NYLON CLEAR



TE Part #320665
PG SPD 22-16 COMM 22-18 MIL 6



TE Part #1-1355200-1
MCP2,8BU-GEH ASSY2P



TE Part #1-1703543-0
2POS,TAB 2.8X0.8,TAB HSG,ASSY



TE Part #2-100103-6
26P.A/L.STRAIN REL.

Documents

Product Drawings

FF 250 TAB 17-13 AWG .015 TPPB

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_928948-4_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_928948-4_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_928948-4_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English