



**Product:** [83319E](#) 

Electronic, 2 C #22 Str SPC, TFE Ins, OA SPC Brd, TFE Tape Jkt, MIL-W-16878/4 (Type E)

 [Request Sample](#)

## Product Description

High Temperature Electronic, 2 Conductor 22AWG (19x34) Silver Plated Copper, TFE Insulation, Overall Silver Plated Copper Braid(85%) Shield, TFE Tape Outer Jacket, MIL-W-16878/4 (Type E)

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

| AWG | Stranding | Material             | No. of Conductors |
|-----|-----------|----------------------|-------------------|
| 22  | 19x34     | SC - Silvered Copper | 2                 |

|                        |   |
|------------------------|---|
| Conductor Count:       | 2 |
| Total Number of Pairs: | 1 |

#### Insulation

| Material                       | Material Trade Name | Nominal Wall Thickness |
|--------------------------------|---------------------|------------------------|
| PTFE - Polytetrafluoroethylene | Teflon®             | 0.01 in                |

#### Color Chart

| Number | Color |
|--------|-------|
| 1      | White |
| 2      | Black |

#### Outer Shield Material

| Type  | Material             | Coverage [%] |
|-------|----------------------|--------------|
| Braid | SC - Silvered Copper | 85 %         |

#### Outer Jacket Material

| Material                       | Material Trade Name | Nominal Diameter | Nominal Wall Thickness |
|--------------------------------|---------------------|------------------|------------------------|
| PTFE - Polytetrafluoroethylene | Teflon®             | 0.143 in         | 0.011 in               |

### Electrical Characteristics

#### Conductor DCR

| Nominal Conductor DCR | Nominal Outer Shield DCR |
|-----------------------|--------------------------|
| 14.6 Ohm/1000ft       | 5.7 Ohm/1000ft           |

#### Capacitance

| Nom. Capacitance Conductor to Conductor | Nom. Capacitance Conductor to Other Conductor to Shield |
|-----------------------------------------|---------------------------------------------------------|
| 29.9 pF/ft                              | 49.2 pF/ft                                              |

#### Inductance

| Nominal Inductance |
|--------------------|
| 0.138 µH/ft        |

#### Current

| Max. Recommended Current [A] |
|------------------------------|
|------------------------------|

|                              |
|------------------------------|
| 5 Amps per conductor at 25°C |
|------------------------------|

Voltage

| Non-UL Voltage Rating |
|-----------------------|
| 600 V RMS             |

Temperature Range

|                       |                 |
|-----------------------|-----------------|
| Operating Temp Range: | -65°C To +200°C |
|-----------------------|-----------------|

Mechanical Characteristics

|                                  |               |
|----------------------------------|---------------|
| Bulk Cable Weight:               | 17 lbs/1000ft |
| Max Recommended Pulling Tension: | 43.8 lbs      |
| Min Bend Radius/Minor Axis:      | 1.5 in        |

Standards

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| CPR Euroclass:          | Eca                                                             |
| Military Specification: | MIL-W-16878/4 (Type E except stranding), (insulated conductors) |
| Other Specification:    | NEMA HP3                                                        |

Applicable Environmental and Other Programs

|                                       |                               |
|---------------------------------------|-------------------------------|
| EU Directive 2000/53/EC (ELV):        | Yes                           |
| EU Directive 2003/96/EC (BFR):        | Yes                           |
| EU Directive 2011/65/EU (ROHS II):    | Yes                           |
| EU Directive 2012/19/EU (WEEE):       | Yes                           |
| EU Directive 2015/863/EU:             | Yes                           |
| EU Directive Compliance:              | EU Directive 2003/11/EC (BFR) |
| EU CE Mark:                           | Yes                           |
| EU RoHS Compliance Date (yyyy-mm-dd): | 2005-01-01                    |
| MII Order #39 (China RoHS):           | Yes                           |

Flammability, LS0H, Toxicity Testing

|                       |               |
|-----------------------|---------------|
| ISO/IEC Flammability: | IEC 60332-1-2 |
| UL voltage rating:    | 600 V RMS     |

Plenum/Non-Plenum

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Part Number

Variants

| Item #         | Color | Putup Type | Length   | UPC          |
|----------------|-------|------------|----------|--------------|
| 83319E 009100  | White | Reel       | 100 ft   | 612825203971 |
| 83319E 0091000 | White | Reel       | 1,000 ft | 612825203988 |
| 83319E 009500  | White | Reel       | 500 ft   | 612825347521 |

|           |                                                                            |
|-----------|----------------------------------------------------------------------------|
| Footnote: | E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'. |
|-----------|----------------------------------------------------------------------------|

Product Notes

|        |                                                                                                         |
|--------|---------------------------------------------------------------------------------------------------------|
| Notes: | Teflon« is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc. |
|--------|---------------------------------------------------------------------------------------------------------|

History

|                      |                                                  |
|----------------------|--------------------------------------------------|
| Update and Revision: | Revision Number: 0.295 Revision Date: 04-08-2020 |
|----------------------|--------------------------------------------------|

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

