

## Twist-Lock® Devices

**Accessories**

for 15 Ampere 2 and 3 Wire Duplex, Single Receptacles and Flanged Devices



NP8I

NP7I

**Single-Gang Wall Plate**

Description	Duplex Plate	Single Rec. Plate 1.406" (35.7) Dia.
	Catalog Numbers	
Brown nylon, smooth.	NP8	NP7
Ivory nylon, smooth.	NP8I	NP7I
Stainless steel 302/304, smooth.	SS8	SS7
Brass, smooth.	SB8	SB7
Aluminum, smooth.	SA8	SA7



HBL5206WO



HBL5221



HBL7423WO



WP1

**Weatherproof Plates****IP44**  
SUITABILITY

Description	Catalog Numbers	
Cast aluminum, for standard horizontal box mount.	HBL5205WO	-
Same as above except FS/FD box mount.	HBL5206WO	-
Cast aluminum vertical FS/FD box mount.	-	HBL7420
Gray thermoplastic, vertical standard box mount, corrosion resistant.	HBL5222*	-
Same as above except yellow.	HBL52CM22*	-
Gray thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL5221*	HBL7423WO
Yellow thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21*	HBL74CM23WO
White thermoplastic, vertical FS/FD box mount, corrosion resistant.	HBL52CM21W*	-

**Weatherproof Plate for  
15A Flanged Inlets and Receptacles****IP44**  
SUITABILITY

Description	Catalog Numbers
Gray thermoplastic, corrosion resistant.	WP1

Notes: All weatherproof plates listed above are UL Listed for wet and damp locations with cover closed. Those with suffix WO are UL Listed with cover open.  
See section K for more information.

\* IP20 Suitability only.