

CUSTOMER LOG



Videos | Blog



DESIGNERS AND MANUFACTURERS OF HEAT TOOLS FOR INDUSTRY

PRODUCTS

PARTS & SERVICE

RESOURCE CENTER

WHERE TO BUY

ABOUT US

CONTACT US



CALL US: 1.800.558.9413

Ask A Question

Request a Catalog/Brochure

Receive Master Updates

Where To Buy

SHARE THIS PAGE



Features

Support Materials

Attachments/Accessories

Economical, light weight, multi-use heat gun

Models

Specifications

- Two heat settings: 500° & 1000° F - Accommodates many automotive and commercial applications.
- Two fan speeds - Low & High (7 & 9 CFM)
- Lightweight - 1 lb. - Easy to hold at any angle for long periods of time, eliminates operator fatigue
- Built-in hand guard - Protects hand and fingers. Recessed switch guards against knocks and bumps
- 3-wire grounded cord set - A positive grounding system for user safety
- UL and CUL listed - Safety agency tested & approved for user safety
- Thermoplastic housing - for high impact durability
- Built-in Stand - Very stable, allows user to set heat gun down in an upright position.
- Use to bend and form plastics, dry body fillers, remove decals, spot dry paint, shrink tubing, packaging and more

Available Models

MODEL NO.	DESCRIPTION
EC-100	Ecoheat Heat Gun, 500° & 1000° F (260 & 538° C), 120V, 10A, 1200W
	Ecoheat Heat Gun Kit, 500° & 1000° F (260 & 538° C), 120V, 10A, 1200W. Kit consists of EC-100 Heat Gun, 7/8" air

EC-100K

reducer attachment,
1 shrink tubing attachment, 1-15/16" and 3-1/8" spreader attachments packed in a durable storage & carrying case.

Specifications

Avg. Air Volume: 7-9 CFM

Avg. Air Velocity: 1020 FPM

Motor: Permanent Magnet

Dimensions: 8.5" L x 3.2" W x 7.7" H

Made in China

Nozzle Opening: 1.2" Dia.

Cordset: 6 ft., 3-wire grounded

Net Weight: 2 lbs.

Shipping Weight: 3 lbs.

HEAT TOOL PRODUCTS
REPAIR SERVICE
DISTRIBUTORS
VIDEOS

ABOUT US
BLOG
SITE MAP
SITE MAP (XML)

Master Appliance Corp.
2420 18th St.
Racine, Wisconsin 53403 USA
Phone: 262.633.7791
Toll Free: 800.558.9413
Fax: 262.633.9745

© 2014 Master Appliance Corp.

POWERED BY
IMAGE MANAGEMENT