


# Features

# Power Module

- Wide input range (3 - 18V)
- Low profile 1.45mm
- Small footprint 3x3mm
- Adjustable output 0.8 to 5.2V
- Up to 120°C ambient temperature with derating
- Integrated solution

## RPL-3.0

**3.0 Amp**  
**10 Pad LGA**  
**Package**



### Description

The RPL-3.0 is a buck converter with integrated inductor in a tiny 3mm x 3mm x 1.45mm thermally-enhanced LGA package. The input range is from 3.0 to 18VDC, allowing 5V and 12V supply rails to be used. The output voltage can be set with two resistors in the range from 0.8V up to 5.2V. The output current is up to 3A and is fully protected against continuous short-circuits, output overcurrent or over-temperature faults. Its high current and small size make the RPL-3.0 ideal for imaging systems, distributed power architectures, portable equipment in telecom as well as industrial applications.

### Selection Guide

Part Number	Input Voltage Range [VDC]	Output Voltage [VDC]	Output Current max. [mA]	Efficiency <sup>(1)</sup> typ. [%]
RPL-3.0	3.0-18.0	0.8-5.2	3000	89

**Notes:**

Note1: Efficiency tested at  $V_{IN}= 12VDC$ , full load and  $V_{OUT}= 3.3VDC$

### Model Numbering

**RPL-3.0-**

Output Current  Packaging <sup>(2)</sup>

**Notes:**

Note2: add suffix "-R" for tape and reel packaging  
add suffix "-CT" for cut tape packaging (refer to "**PACKAGING INFORMATION**")

### Specifications

ABSOLUTE MAX RATINGS (exceeding these ratings may damage the device)				
Parameter	Symbol	Min.	Typ.	Max.
Absolute Maximum Voltage	$V_{IN}$	-0.3VDC		20VDC
	$V_{OUT}$	0VDC		6.5VDC
	$V_{CTRL}$	0VDC		18VDC
	$V_{PG}$	0VDC		5.5VDC
	others <sup>(3)</sup>	-0.3VDC		4VDC
Maximum continuous power losses <sup>(4)</sup>	@ $T_{AMB} = 25^{\circ}C$			2.08W
Junction Temperature	$T_J$			150°C
Lead Temperature				260°C
Storage Temperature		-65°C		+150°C

**Notes:**

Note3: For CTRL absolute max ratings, please refer to "**CTRL and SYNC Operating CONDITIONS**"

Note4: Exceeding maximum allowable power dissipation causes device to enter thermal shutdown which protects device from permanent damage. Refer to "**CHARACTERISTIC CURVES**"



EN55032 compliant



[www.recom-power.com/eval-ref-boards](http://www.recom-power.com/eval-ref-boards)


**Specifications**

**OPERATING CONDITIONS** ( $V_{IN}= 12VDC$ ,  $T_J= -40^{\circ}C$  to  $+125^{\circ}C$ , unless otherwise noted, typical values are at  $T_J= +25^{\circ}C$ )

Parameter	Symbol	Condition	Min.	Typ.	Max.
Input Voltage Range	$V_{IN}$		4VDC		18VDC
UVLO threshold rising			3.2VDC	3.6VDC	3.9VDC
UVLO threshold falling				3.1VDC	
UVLO threshold hysteresis				500mV	
Output Voltage Range	$V_{OUT}$		0.8VDC		5.2VDC
Output Current Range	$I_{OUT}$		0A		3A
Standby current	$I_{IN}$	$V_{CTRL} = 0VDC$			15 $\mu$ A
Quiescent current	$I_Q$	$V_{FB} = 0.85VDC$ , no switching		1.2mA	
Leakage current	$SW_{LKG}$	$V_{CTRL} = 0VDC$ ; $V_{SW} = 12VDC$			1 $\mu$ A
Switching frequency	$f_{SW}$		1870kHz	2200kHz	2530kHz
Feedback voltage	$V_{FB}$		788mV	800mV	812mV
Output load regulation		0-100% load @ 3.3V <sub>OUT</sub>	-0.5%		+0.5%
V <sub>CC</sub> regulator	$V_{CC}$			3.3VDC	
V <sub>CC</sub> load regulation		$I_{CC} = 20mA$		3%	
Rise time		$V_{OUT}$ from 10% to 90%		1.65ms	

**Typical Application**


$V_{IN}= 4-18VDC$ ;  $V_{OUT}= 3.3VDC$ ,  $I_{OUT}= 3A$



**Notes:**

Note5: A 10 $\mu$ F input capacitor ( $C_{IN}$ ) is required to absorb the input switching current. A 22 $\mu$ F output capacitor ( $C_{OUT}$ ) is mandatory. To get stable regulation use for  $R_1$  and  $R_2$  1% or 0.1% resistors,  $R_4$  should be 1k $\Omega$ m. RECOM recommends low ESR X5R or X7R ceramic caps.

**Safe Operating Area**



**Specifications**

**CTRL OPERATING CONDITIONS** ( $V_{IN}= 12VDC$ ,  $T_J= -40^{\circ}C$  to  $+125^{\circ}C$ , unless otherwise noted, typical values are at  $T_J= +25^{\circ}C$ )

Parameter	Symbol	Condition	Min.	Typ.	Max.
CTRL rising threshold	$V_{CTRL\_RISING}$		1.1VDC	1.2VDC	1.3VDC
CTRL falling threshold	$V_{CTRL\_FALLING}$		0.96VDC	1VDC	1.04VDC

**POWER GOOD OPERATING CONDITIONS** ( $V_{IN}= 12VDC$ ,  $T_J= -40^{\circ}C$  to  $+125^{\circ}C$ , unless otherwise noted, typical values are at  $T_J= +25^{\circ}C$ )

Parameter	Symbol	Condition	Min.	Typ.	Max.
OV rising threshold	$V_{FB}$	$PG_{OVHI}$ fault	110%	115%	120%
OV falling threshold	$V_{FB}$	$PG_{OVL0}$ good		110%	
UV rising threshold	$V_{FB}$	$PG_{UVHI}$ good	85%	90%	95%
UV falling threshold	$V_{FB}$	$PG_{UVLO}$ fault		80%	
Sink current capability	$V_{PG}$	$sink_{current} = 4mA$		0.4VDC	0.6VDC

**PROTECTIONS**

Parameter	Symbol	Condition	Min.	Typ.	Max.
Over current Limitation	$L_{Limit}$	current monitor via internal MOSFET $R_{DS(on)}$	3A	3.3A	3.9A
OVP threshold	$V_{OVP}$	if $V_{FB}$ is greater than $V_{OVP}$ , for $t_{OVP}$ , device will enter hiccup mode	110%	115%	120%
OVP hysteresis		disabled during soft start		5%	
Over voltage delay	$t_{OVP}$	if $V_{FB}$ is greater than $V_{OVP}$ , for $t_{OVP}$ , device will enter hiccup mode		2 $\mu$ s	
Output pin OVP	$V_{OVP\_FB > 115\%}$		5.7VDC	6VDC	6.3VDC
Absolute OVP hysteresis				50mV	

**THERMAL OPERATING CONDITIONS** ( $V_{IN}= 12VDC$ ,  $T_J= -40^{\circ}C$  to  $+125^{\circ}C$ , unless otherwise noted, typical values are at  $T_J= +25^{\circ}C$ )

Parameter	Symbol	Condition	Min.	Typ.	Max.
Operating Junction Temperature	$T_J$		-40 $^{\circ}C$		+125 $^{\circ}C$
Thermal Resistance <sup>(6)</sup>	$R_{th\_JA}$ $R_{th\_JC}$	$J_{AMB}$ $J_C$		65K/W 30K/W	
Thermal shutdown		hysteresis		150 $^{\circ}C$ 20K	

**Notes:**

Note6: Tested with RECOM evaluation module: [RPL-3.0-EVM-1](#)

**OUTPUT VOLTAGE SETTING**

The external resistor divider sets the output voltage. Choose the R1 resistance. R2 can be estimated with Equation:

$$R2 = \frac{R1}{\frac{V_{OUT}}{0.8VDC} - 1}$$




Table below lists recommended resistor values for common Vout:

$V_{OUT}$ [V]	$R1$ [k $\Omega$ ]	$R2$ [k $\Omega$ ]	$C_{FF}$ [pF]	$C_{OUT}$ [pF]
1	47	187	22	22
1.2	47	93.1	22	22
1.5	47	53.6	22	22
1.8	47	37.4	22	22
2.5	47	22	39	22
3.3	47	15	39	22
5	47	8.87	39	22





Where  $V_{OUT}$  is the output voltage. The output voltage feedback gain is determined by:

$$G_{FB} = \frac{R2}{R1 + R2}$$



To stabilize the system and optimize the load transient response, place a feed-forward capacitor ( $C_{FF}$ ) in parallel with R1. Upper table shows the values of feedback resistors and feed-forward capacitors for common output voltages.

Specifications

TYPICAL PERFORMANCE CHARACTERISTICS ( $V_{OUT}= 1.8VDC, T_J= +25^{\circ}C$ ; tested with RECOM evaluation module: RPL-3.0-EVM-1)





TYPICAL PERFORMANCE CHARACTERISTICS ( $V_{OUT}= 3.3VDC, T_J= +25^{\circ}C$ ; tested with RECOM evaluation module: RPL-3.0-EVM-1)







continued on next page

Specifications

TYPICAL PERFORMANCE CHARACTERISTICS ( $V_{OUT} = 3.3VDC$ ,  $T_J = +25^\circ C$ ; tested with RECOM evaluation module: RPL-3.0-EVM-1)



TYPICAL PERFORMANCE CHARACTERISTICS ( $V_{OUT} = 5VDC$ ,  $T_J = +25^\circ C$ ; tested with RECOM evaluation module: RPL-3.0-EVM-1)



**Specifications**


**SAFETY AND CERTIFICATIONS**

<b>Certificate Type (Safety)</b>	<b>Standard</b>
RoHS2	RoHS 2011/65/EU + AM2015/863

**DIMENSION AND PHYSICAL CHARACTERISTICS**

Parameter	Type	Value
Material		plastic
Dimension (LxWxH)		3.00 x 3.00 x 1.45mm
Weight		0.1g typ.

**Dimension Drawing (mm)**



**Pad Information**

Pad #	Function	Description
1	CTRL	CTRL pin. Connect to +Vin when not used.
2	+Vin	Input voltage. Connect using wide PCB traces. Requires Cin to decouple input rail.
3, 4	-Vin	System ground. Reference ground of the regulated output voltage. Requires special consideration during PCB layout. Connect to -Vin with copper traces and vias.
5	Vout	Output voltage. Connect external bypass capacitors between this pin and GND close to the pins.
6	+Sense	Output voltage sense pin
7	FB	Feedback input. Used to set the output voltage between 0.8V and 5.2V
8	GND	Analog ground
9	VCC	Internal 3.3VDC LDO regulator output.
10	PG	Power good output.

Tolerances: x.x= ±0.1mm  
x.xx= ±0.05mm

**Specifications**


**SOLDERING**

Wave or Reflow etc.

Profile Feature	PB-Free Assembly
<b>Preheat</b>	
minimum Temperature (TS_min)	155°C
maximum Temperature (TS_max)	245°C
Time (tS)	100s-300s
<b>Liquidus</b>	
Temperature (TL)	217°C
Time (tL)	30-60s
<b>Peak Temperature (TP)</b>	
Peak Temperature (TP)	245°C
Time remaining around Peak Temperature	10s
<b>max Ramp Down Rate (from Ts_max to TP)</b>	
max Ramp Down Rate (from Ts_max to TP)	5K/s
<b>max Ramp Up Rate</b>	
max Ramp Up Rate	3K/s
<b>max time from 25°C to Peak Temperature (TP)</b>	
max time from 25°C to Peak Temperature (TP)	8min

- 1 Pb-Free assembly is recommended according to JEDEC J-STD020.
- 2 Ensure that the peak reflow temperature does not exceed 240°C ±5°C as per JEDEC J-STD020
- 3 The reflow time period during peak temperature of 240°C ±5°C should not exceed 30 seconds.
- 4 Reflow time above liquidus (217°C) should not exceed 150 seconds.
- 5 For solder paste use a standard SAC Alloy such as SAC 305, type 3 or higher.
- 6 Other soldering methods (e.g. vaporphase) are not verified and have to validate by the customer on his own risk.



**Solder Pofil**



**PCB LAYOUT SUGGESTION**


Efficient PCB layout is critical for stable operation. For the best results, see Figure below and follow the guidelines below:

1. Keep the connection of the input ground and -V<sub>IN</sub> as short and wide as possible.
2. Ensure that all feedback connections are short and direct.
3. Place the feedback resistors as close as to the chip as possible.
4. Route sensitive analog areas such as FB away from SW.
5. Place enough vias around the chip to improve thermal performance.



**Specifications**

**BLOCKDIAGRAMM**



**PACKAGING INFORMATION**

Parameter	Type	Value
Packaging Dimension (LxWxH)	reel (diameter + width)	Ø330.0 + 12.0mm height
	tape and reel (carton)	370.0 x 350.0 x 53.0mm
	moisture barrier bag ("-CT")	100.0 x 100.0 x 30.0mm
Packaging Quantity	tape and reel	500pcs
	tube ("-CT")	10pcs
Tape Width		12mm
Storage Temperature Range		-55°C to +125°C
Storage Humidity	non-condensing	95% RH max.

The product information and specifications may be subject to changes even without prior written notice. The product has been designed for various applications; its suitability lies in the responsibility of each customer. The products are not authorized for use in safety-critical applications without RECOM's explicit written consent. A safety-critical application is an application where a failure may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The applicant shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.