



Service Entrance Fittings

T&B Catalog Number:

2116-TB

UPC Number:

78621002116

Status:

Active

Description:

1/2" Service Entrance Cable Connector, Die Cast Zinc; Gland-Steel-Electro Zinc Plated; Retaining Ring-Stainless Steel; Bushing-Neoprene. Cable opening-.235 x .500.

Features

Neoprene bushing, resists oil and water; grips cable the full length of the bushing providing adequate strain relief without damaging outer jacket.

Taper threaded body, stainless steel retaining ring protects cable jacket against abrasion; reduces installing torque effort.

Rugged ribbed steel gland construction, suitable for Type SE & USE service entrance cable.

Application

To connect service entrance cables to a meter box or an enclosure.

General

Material	Die Cast Zinc
Cable Opening (inches)	.235 x .500

Dimension Information

Hub Size (inches)	1/2
Dimension A (inches)	1 11/16
Dimension B (inches)	5/8
Dimension C (inches)	1
Dimension D (maximum) (inches)	0.235
Dimension E (maximum) (inches)	0.500
Dimension E (minimum) (inches)	0.350
Dimension F (inches)	9/16
Dimension G (inches)	1 1/8
Dimension H (inches)	1 1/8

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	14 lbs. per 100

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:
E 17583

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com