



## Flexible Conduits & Fittings

### T&B Catalog Number:

CYLT-10B.50

### UPC Number:

78620995480

### Status:

Active

### Description:

Fine profile medium wall very flexible black conduit. (CYL) Material - polyamide 6, conduit size NW - 10.

### Application

Machine

Installation Industries

### Characteristics

Very good flexibility

Good impact strength, also at low temperatures and dry conditions

Self-extinguishing, free from halogens and cadmium

### General

Material	Polyamide 6
Material-Conduit Core	Non-Metallic
Color	Black
System	PMAFLEX
Compatible With	PMAFIX Pro, PMAFIX, PMA Smart Line, PMAGRIP

### Dimension Information

Conduit Size (inches)	5/16
Conduit Size NW (mm)	10
Conduit Size Metric (mm)	12
Inside Diameter (inches)	0.38
Outside Diameter (inches)	0.51
Inside Diameter (mm)	9.6
Outside Diameter (mm)	13
Static Radius (mm)	20
Rec. Fitting Thread-Metric	M12 x 1.5
Rec. Fitting Thread-PG	10

### Technical Information

Temperature Range-Continuous (Celsius)	-40 to +105
Temperature-Short-Term (Celsius)	160
Fatigue Life	High
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

### Packaging

T&B Order Multiple	1
T&B Inner Pack	1
Package in Units	20
T&B Sold in UOM	Each
T&B Weight Per UOM	3.3 lbs. Each

### Application Support

PMA Reference Guide	Available on Website
PMA Conduit Guide	Available on Website
Product Overview-PMAFLEX Conduits	Available on Website

## Certifications

RoHS Compliance Yes

## Certifications



### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)