

Ceramic Capacitors

Fixed Ceramic Capacitors

Part Number :**C3225X5R0J226K/2.50**

Product Name :

Multilayer Ceramic Chip Capacitors

- General Purpose

View Datasheet

TDK Series Name :**C Series**

Application :

Electronics equipment, automation equipment, measurement equipment, Charge pump, etc.

Mobile communications equipment, Automotive electronics, Hybrid ICs, Decoupling, Smoothing,

Office Test and

Function :

It has no polarity. High reliability is guaranteed.It can be adapted for various circuit such as transmission, amplification and feed through.

Description :

Small Size High Capacitance Multilayer Ceramic Chip Capacitor. It has no polarity. High reliability is guaranteed.

Submit Sample Request

Check Distributor Inventory

Print Page



Additional Search Tools:

Application	Catalog	SEAT	CCV	TVCL	Tech Notes
Property Name		Property Description			
Product Lifecycle Stage		Production			
Part Number Replacement		No Data Available.			
Lead (Pb) Free		Yes			
Surface Mount		Yes			
EIA Size Code		1210			
Size Code		3225			
Body Length (L)		Min 3 mm			
Body Length (L)		Nom 3.2 mm			
Body Length (L)		Max 3.4 mm			
Body Breadth (W)		Min 2.2 mm			
Body Breadth (W)		Nom 2.5 mm			
Body Breadth (W)		Max 2.8 mm			
Body Height (T)		Min 2.2 mm			
Body Height (T)		Nom 2.5 mm			
Body Height (T)		Max 2.8 mm			
Terminal Width (B)		Min 0.2 mm			
Terminal Spacing (G)		Min 1 mm			
Temperature Characteristics		X5R			
Temperature Characteristic		Min -15 %			
		Max 15 %			
Category Temperature Range		Min -55 C			
		Max 85 C			
Rated Voltage Code		0J			
Rated Voltage		Max 6.3 V			
Rated Voltage Classification		DC			
Withstanding Voltage		Nom 15.75 V			
Withstanding Voltage Class		DC			
Rated Capacitance		Nom 22000000 pF			
Capacitance Tolerance Code		K			
Capacitance Tolerance (Value)		Min No Data Available.			
		Max No Data Available.			
Capacitance Tolerance (%)		Min -10 %			
		Max 10 %			
Q		Min No Data Available.			
Measurement Frequency of	Q	Nom No Data Available.			
Insulation Resistance		Min 4 MOhm			
Dissipation Factor		Max No Data Available.			
Frequency of Dissipation Factor		Nom 120 Hz			
Soldering Method		Reflow, Manual			
Storage Temperature Range		Min 5 Cel			
		Max 40 Cel			
Packing		Blister (Plastic)Taping [180mm Reel]			
Minimum Package Qty		Nom 1000 Pcs			
Minimum Order Qty		Nom 1000 Pcs			
Return Status		STD			
Disclaimer: This information is to be used for reference purposes only and is subject to change by TDK without notice. It reflects an overview of the product characteristics/performance for the particular part number. For product specification information, please refer to TDK's general product specification. Please note that this standard part is not designed or warranted to meet any specifications of any intermediate or end user different from or in addition to the specifications set fort in TDK's general product specification. Note also that this standard part has not been specially designed or manufactured for, nor is it intended or warranted for use in , or permitted to be resold for, specialized applications such as aviation, medical, and/or governmental/military applications (collectively, "Excluded Applications").					

© TDK U.S.A. Corporation 2011. » Privacy Statement » Careers » Site Map

TDK Logo is a trademark or registered trademark of TDK Corporation.