

**VPMS (Verschlusschraube Messing)  
VP M16-MS65**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

Type	VP M16-MS65
Order No.	<a href="#">1777730000</a>
Version	*UNDEFINED TEXT*, Blanking plug, M 16, 5 mm, Brass, nickel-plated
GTIN (EAN)	4032248158003
Qty.	100 pc(s).

## Data sheet

### VPMS (Verschlusschraube Messing) VP M16-MS65

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Dimensions and weights

Length	8 mm	Length (inches)	0.315 inch
Height	8 mm	Height (inches)	0.315 inch
Net weight	5.21 g	Diameter	18 mm

### Temperatures

Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Operating temperature, max.	100 °C	Operating temperature, min.	-40 °C

### Classifications

ETIM 3.0	EC000032	ETIM 4.0	EC000032
ETIM 5.0	EC000032	ETIM 6.0	EC000451
UNSPSC	30-21-18-01	eClass 5.1	27-14-91-10
eClass 6.2	27-14-91-10	eClass 7.1	27-14-91-10
eClass 8.1	27-14-91-10	eClass 9.0	27-14-44-33
eClass 9.1	27-14-44-33		

### Product information

Descriptive text ordering data      Other versions available on request. The blanking plugs must be tightened "hand-tight" with the screwdriver.

### Approvals

Approvals



ROHS      Conform

### Downloads

Brochure/Catalogue	<a href="#">CAT 3 HDC 17/18 EN</a> <a href="#">CAT 8 SAI 15/16 EN</a> <a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Engineering Data	<a href="#">STEP</a>

**Data sheet**

**VPMS (Verschlusschraube Messing)  
VP M16-MS65**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

