


product data sheet

item no. 5D.S06.9055.0

earth terminal WTN 6 PE

earth terminal WTN 6 PE rated voltage 1000 V, screw connection, number of levels 1, number of clamp positions per level 2, nominal cross section 6 mm², connectable conductor cross section fine stranded without cable end sleeve 0,2mm² - 6mm², mounting method DIN rail (top hat rail), color green/yellow, width/grid dimension 8 mm, inflammability class of insulation material acc. with ul94 V0



item no.	5D.S06.9055.0
EAN	4049088725340
order unit	50 piece(s)

certificates / approvals



technical data

general

nominal cross section	6 mm ²
color	green/yellow
number of levels	1
number of clamp positions per level	2
width/grid dimension	8 mm
insulating housing	PA
inflammability class of insulation material acc. with UL94	V0
mounting method	DIN rail (top hat rail)
terminal blocks for electrical installations	yes
Anschlussart	screw connection
Anzahl der Klemmstellen je Etage	2
Montageart	DIN rail (top hat rail)
Brennbarkeitsklasse des Isolierstoffs	V0
Reihenklemmen für Installationsverteiler	yes

technical data

rated voltage	1000 V
rated impulse voltage	8 kV
pollution degree	3
closing plate required	yes
type of insulation material	thermoplastic
length	40.7 mm
width	8 mm
height	42 mm

connection data

connection type	screw connection
connection type 1	screw connection
minimum cross section solid	0.2 mm ²
maximum cross section solid	10 mm ²
minimum cross section fine stranded	0.2 mm ²
maximum cross section fine stranded	6 mm ²
minumum conductor cross section (flex., stranded) with cable end sleeve	0.5 mm ²
maximum conductor cross section (flex., stranded) with cable end sleeve	6 mm ²
wire strip length	12 mm
torque conductor mounting	1.2 Nm

technical data UL/CSA

cross section UL	20-8 AWG
voltage UL	600 V
cross section CSA	20-8 AWG
voltage CSA	600 V

